



Keep it fresh

BreadCast™

BreadCast™ is a non-oriented polypropylene film produced by a flat die, chill roll process. It features excellent flexibility, smoothness and sealability. BreadCast™ is primarily used by bakeries for packaging of bread and pastry using automatic filling machines.

Characteristics:

BreadCast™ packaging films and bags optimize bread and pastry's shelf life, nutritional values and appearance. BreadCast™ combines exceptional mechanical properties for faster packing and better handling during transportation and display, combined with superior transparency and superb printability that meet customers' desire for a clear view of the product.

Typical Properties:

Property	Units		ASTM#	Value	Value	Value
Thickness	Micron			23	30	40
Tensile Strength	MPa	MD	D882	47	69	63
		TD		38	41	44
Elongation at Break	%	MD	D882	618	666	704
		TD		766	858	832
Coefficient of Friction	Film to film		D1894	0.2±0.05	0.2±0.05	0.2±0.05
Haze	%		D1003	3.3	3.4	3.8

Treatment level ≥38 Dynes/cm (ASTM-D2578)

Food contact: this film is made of materials suitable for food contact in accordance to FDA and/or EEC regulations. Specific documents will be provided upon request.

The information contained herein is current but may be subject to change. It is offered as a guide only, and is not intended to replace any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge and experience become available. Since we cannot anticipate all variations in actual end-use conditions, ROP makes no warranties and assumes no liability in connection with any use of this information. All rights reserved.